

Leica Geosystems

How to use Leica mySecurity



Contents

1. Introduction.....	2
2. Adding the product to myWorld.....	2
3. Activating mySecurity	3
4. FlexField Status Info	6
5. Report as Stolen	7
6. Locate stolen instrument.....	8

1. Introduction

This document describes how to activate mySecurity on a Flexline TS03/07 instrument.

mySecurity is a unique cloud-based theft protection provided by Leica Geosystems.

mySecurity gives you total peace of mind if your instrument is ever stolen. A locking mechanism is available to ensure that the device is disabled and can no longer be used.

All Flexline users can activate this feature within the Leica customer portal - **myWorld**.

2. Adding the product to myWorld

First, register your Flexline Total Station within myWorld - myProducts.

Only products that are available in myWorld - myProducts can be added to mySecurity.

Then go to myTrusted Services - mySecurity.

myApplications > myTrustedServices > **mySecurity**

My Security



Leica Geosystems - mySecurity

Leica Geosystems mySecurity delivers you total peace-of-mind in knowing that if your instrument is ever stolen, a locking mechanism is available to ensure that the instrument is disabled and can no longer be used.

Help

	Product	Serial No.	My Reference	Activated	Renewal	Stolen
	TS09ultra, 2" r.tot.st.,2 full keyb	1300009				
	TS16 I R1000, basic total st.	3013446		06.02.2019	06.02.2020	
	TS07 3" R1000, total station	3301194				

Details

Remove

Add

For each product available on the list, the Activation & Renewal date is displayed, and the Stolen status, in case of the instrument has been flagged as stolen.

Press to add a new product to mySecurity.

Press to delete one product from mySecurity.

Add Product

Product

TS07 3" R1000, total station | S/N:3301194

Click **OK** to accept.

3. Activating mySecurity

The instrument needs to be connected to the PC via USB or serial cable.

Select your instrument and press

After pressing the “Details” button, next screen will be displayed:

myApplications > myTrustedServices > mySecurity

Overview

Back

Help

General



Product	TS07 3" R1000, total station	Article No.:	868841
My Reference:		Delivery Date	02.11.2018
Serial No.:	3301194	Equipment No.:	8432875
Status:			

mySecurity



mySecurity... : No

New mySecurity Renewal

07.05.2019

In 3 months

In 6 months

In 12 months





Press Set to activate mySecurity on the connected product. Press Deactivate to deactivate mySecurity on the connected product.

Please make sure that the product is connected to your computer and only disconnect once the activation is complete. Please use Internet Explorer for successful operation.

Page 3 of 8

In section **mySecurity**, the status is disabled. To activate it, the user must define a connection interval to myWorld e.g. every 3, 6 or 12 months.


Press once **mySecurity renewal** has been selected.



Note:

- An installation program may be downloaded and installed on your computer automatically.
- The software, automatically scans all the connection ports, in order to detect which port the instrument is connected.
- Users can manually scan, in case the automatic scan is not successful, pressing "Scan" button.
- Connection settings can be selected by user, or set it by default, pressing "Defaults" button.
- Additionally, an information message will be displayed on the Total station informing if the "mySecurity" protection has been enabled/extended/disabled

After pressing "Connect", picture below will be displayed.



Press "Close".


Automatically the program will lead us to overview screen. Press  button to update mySecurity information.



If the instrument is not re-connected on time (or before) to myWorld the instrument gets blocked and cannot be used anymore unless it is connected to myWorld to repeat this procedure to set a new mySecurity renewal date.


4. FlexField Status Info

On the Flexline instrument, go to Tools – Info – Page 5 to check **mySecurity Renewal Date**.




Up until this date the instrument needs to be re-connected to the myWorld portal to renew the mySecurity date.

During start up, a certain time before the renewal date is due, the following message will pop up:



When the number of remaining days has been exceeded, the next message will pop up:



5. Report as Stolen

In mySecurity, an instrument can be reported as Stolen.

Overview

Back

Help

General



Product:	TS07 3" R1000, total station	Article No.:	868841
My Reference:		Delivery Date:	07.02.2019
Serial No.:	3301194	Equipment No.:	8432875
Status:			Report as...

mySecurity



mySecurity...	Yes
Activation Date	08.02.2019
Next mySec...	08.05.2019

New mySecurity Renewal

08.05.2019

In 3 months

In 6 months

In 12 months




Press Set to activate mySecurity on the connected product. Press Deactivate to deactivate mySecurity on the connected product.
Please make sure that the product is connected to your computer and only disconnect once the activation is complete. Please use Internet Explorer for successful operation.

Set

Deactivate

After pressing the "Report as Stolen" button, a warning will pop up to confirm that the device as stolen.

Please Confirm!

Are you sure to report this product as stolen? If you report this product as stolen it will be locked once the mySecurity renewal date is reached.
Please note, that products reported as stolen can only be re-activated by your local Leica Geosystems representative.

OK

Cancel

If accepted, instrument status changes to **Stolen!**.

General



Product:	TS07 3" R1000, total station
My Reference:	
Serial No.:	3301194
Status:	Stolen!

mySecurity



mySecurity...	Yes
Activation Date	08.02.2019
Next mySec...	08.05.2019

After reporting as stolen, if the instrument is ever brought into an Authorized Leica Service Centre it will be known that it is stolen, and the local Authorities will be informed.

6. Locate stolen instrument

Once a stolen instrument was attempting to connect to myWorld, the IP address will be logged and used to locate the instrument.

The status changes from 'Stolen' to 'Located' and a new icon 'Show Location' becomes available:

General



Product: TS07 3" R1000, total station
My Reference:
Serial No.: 3301194
Status: **Located!**

Article No.:
Delivery Date:
Equipment No.:
Show Location

By selecting 'Show Location' button, a pop-up window will appear showing the date and time of the location as well as the IP address. The location will be shown on a map by pressing the link.



The location of the stolen instrument will be shown in a map:

Check 178.192.143.189 Google Maps™ Windows Live Maps™ Yahoo Maps™ Two Maps Overview Map

Amriswil, Switzerland

IP Address	178.192.143.189	City	Amriswil	Country Flag		DMA Code	n/a
Provider	Bluewin	State (Code)	Sankt Gallen (15)	Latitude	47.547	Area Code	n/a
Hostname	189-143.192-178.cust.bluewin.ch	Country	Switzerland	Longitude	9.2984	Postal Code	n/a
Timezone	Europe/Zurich	Continent	Europe	TLD	CH	GMT Offset	1